

TECHNICAL DATA SHEET

PRODUCT: Rainwater mouldings – joints, running outlets, brackets etc...

REFERENCE: Round, Square, Ogee, Deep, Commercial Superdeep 170
W = White, BL = Black, *Caramel = C, Grey = GR, Anthracite
RAL7016 Grey = AG, Brown = BR, Cast Black = CB
See literature for full range availability

A. Materials

Standard injection mouldings are manufactured from a virgin PVC formulation blend.

B. Quality Standards

All mouldings are manufactured in accordance with BS EN 1462:2004 (Brackets for Eaves Gutters) and are covered by Kite Mark approval (KM508760).

In addition, the production facility has been awarded BS EN ISO 9001, ISO14001, OHSAS18001, ISO50001 and BES6001 Responsible Sourcing certification.

All profiles carry a 10-year guarantee and have been assessed for quality, durability [weather resistance] and performance. In particular gutter loading has been assessed in accordance with BS 4576:1998 and found to exceed the specified test loads.

*Excludes Caramel

Cast Black system has a spray applied finish to recreate an authentic cast effect. It also includes bespoke shoe, pipe sockets and pipe clips to complete the system.

Where appropriate, mouldings include sealing gaskets and accept gutter or pipe by push fit or snap-on connection.

Hoppers, rodding access and diverters for water collection devices are available.

Recommended fixing procedures should be followed (see www.kayflow.co.uk for further info).