

## 92A PVC-Degreaser

Revision: 30/08/2017

Page 1 from 1

### Technical data

Basis	Solvent mixture
Consistency	Fluid
Density	0,85 g/ml
Application temperature	5 °C → 25 °C

(\*) these values may vary depending on environmental factors such as temperature, moisture, and type of substrates.

### Product description

92A PVC-Degreaser is a colourless, low boiled mixture of solvents.

### Properties

- High degreasing power
- dry fast

### Applications

- Cleaning and degreasing of subfloors and materials.
- Degreasing of PVC.
- Removal of fresh, non cured adhesive stains.

### Packaging

*Colour:* colorless

*Packaging:* 1L (metal) tin

### Shelf life

12 months in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C.

### Substrates

*Substrates:* hard PVC

*Nature:* clean, dry, dust-free.

*Surface preparation:* No pretreatment required.

### Application method

*Application method:* Apply 92A PVC-Degreaser with a cloth soaked in product. Always work with a clean cloth to avoid contamination of the surface. Replace if necessary. Always wipe in one direction. After cleaning the surface let dry sufficiently before applying the kit. Remove cured sealant with Sealant Remover and spatula or stiff brush.

### Health- and Safety Recommendations

Take the usual labour hygiene into account. Consult label for more information. Use only in well-ventilated areas. Do not smoke. Wear gloves. In case of insufficient ventilation it is appropriate to wear respiratory protection.

### Remarks

- Due to the wide variety of possible plastics and paints and to avoid damage to the surface, a preliminary compatibility test is recommended.

Remark: This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.