

Sealing Strip

Product description

Sealing Strip is a self-adhesive sealing tape for waterproof sealing joints along bath, shower tray, wash-basin, countertop, sink, floor and tiles. Quick and easy to apply alternative to traditional sealants.

Properties

- Watertight
- Easy to apply
- Very good adhesion on many materials
- Tear resistant
- Colourfast
- No drying time, continue working immediately
- Solvent free

Applications

- Waterproof sealing of joints along bath, shower tray, wash-basin, countertop, sink, floor and tiles.
- As an alternative to traditional sealants
- Only for interior use

Technical data

Carrier	Thermoplastic elastomer
Adhesive layer	Butyl Rubber
Release liner	Siliconized foil
Application temperature	+5°C → +30°C
Thickness (Carrier & Adhesive)	1.70 mm

Footnote: These values may vary depending on environmental factors such as temperature, moisture, and type of substrates.

Substrates

- Substrate condition
The surface must be rigid, clean, dry, free of dust and grease. Ensure that frost or condensation are absent on the surface.
- Substrate preparation
Carefully degrease the surface with Soudal Surface Cleaner or acetone (the latter is not suitable for plastics). A preliminary adhesion test on every substrate is recommended.
- Substrate types
The most common substrates in bathrooms and kitchens: bath, shower tray, wash-basin, sink, floor and tiles. Not suitable for PE, PP, PTFE and bitumen.

Sealing Strip

Application method

■ Application method

Cut the Sealing Strip to size and take 1 cm extra as a margin. If the strip is a bit stiff, it can be softened by gently warming it up on the radiator or using a hair dryer. Fold the strip in half over its entire length and remove a small section of the release liner. Apply the strip to the corner of the longest joint and press firmly. Remove the remaining release liner and continue to press firmly and evenly without stretching the strip. Cut off the excess strip at the end of the joint. Adhere the strips in the corners over one another, then cut the overlapping parts in a 45° angle, remove the loose pieces and press the corner firmly again. To obtain a better adhesion you can heat the strip with a hairdryer for 10 sec. immediately after application. Check if the Sealing Strip adheres well everywhere (especially in tile joints) and wait 24 hours before using the sanitary ware.

■ Cleaning method

Adhesive residues can be removed with Soudal Remover CT or Soudal Surface Cleaner.

■ Repair method

Repair with the same material.

Health- and Safety Recommendations

Take the usual labour hygiene into account. Consult the packaging label and safety data sheet for more information.

Packaging/Logistics

Colour: White

Packaging: Roll

Length (m): 3.35

Width (mm): 22, 38

Thickness (mm): 1.7

Shelf life: At least 24 months in original, unopened packaging at a cool and dry storage place, between +5°C and +40°C., Storage above +50°C may lead to difficulties in removing the release liner.

Remarks

- Not suitable for expansion and dilatation joints.
- The applied pressure and not the duration of the pressure will determine the ultimate strength of the bond.

This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. It is general in nature and does not constitute any liability. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application. In every case it is recommended to carry out preliminary experiments. The manufacturer reserves the right to modify products without prior notice.