



# Turbo Decorators Caulk

## Product description

Turbo Decorators Caulk is a one-component, quickly paintable, plasto-elastic sealant based upon acrylic dispersion.

## Properties

- Easy to apply
- Easy to finish
- Paintable after 5 minutes
- Paintable with many types of paint
- Colourfast and waterproof after curing

## Applications

- Finishing of seams and gaps on porous surfaces which need be painted
- Finishing of various board and ceiling lists and decorative elements such as moldings.
- For filling and repair of cracks and drilling holes in walls and ceilings (plasterboard, concrete, stone, ...).



## Technical data

Base	Acrylic dispersion
Consistency	Paste
Curing system	Physical drying
Skin formation	ca. 20 minutes
Density	ca. 1.72 g/ml
Shrinkage after curing	ca. 30%
Application temperature	+5°C → +30°C
Temperature resistance	-20°C → +80°C

*Footnote: Skinning time and curing speed may vary depending on environmental factors such as temperature, moisture, and type of substrates.*

## Substrates

- Substrate condition  
The surface must be rigid, clean, dry, free of dust and grease.
- Substrate preparation  
Highly porous surfaces should be primed with diluted Turbo Decorators Caulk (1 part Turbo Decorators Caulk + 2 parts water).
- Substrate types  
Turbo Decorators Caulk has a good adhesion to following substrates: all common porous building substrates. Turbo Decorators Caulk has no good adhesion or is not suitable for natural stone, bituminous substrates, glass, metal. We recommend a preliminary adhesion and compatibility test on every surface.

## Application method

- Application method  
Do not apply when rain or frost is imminent during the curing process.
- Application tools  
With a manual, pneumatic or battery caulking gun.



# Turbo Decorators Caulk

- Cleaning method  
Before curing, Turbo Decorators Caulk can be removed with water from substrates and tools.
- Finishing method  
Finish with a wet spatula or putty knife.
- Repair method  
Repair with the same material.

## Health- and Safety Recommendations

Take the usual labour hygiene into account. Consult the packaging label and safety data sheet for more information.

## Packaging/Logistics

Colour: Please consult the product catalogue, the Soudal website or a Soudal representative.

Packaging: Please consult the product catalogue, the Soudal website or a Soudal representative.

Shelf life: 12 months in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C, Protect against frost.

## Remarks

- Do not use in applications where continuous water immersion is possible.
- Paintable with most paints, even highly filled and covering paints of type 2010.
- The paint must be sufficiently elastic to allow application on a plasto-elastic sealant.
- Given the great diversity in available paints, we recommend to do a compatibility test prior to application.
- Turbo Decorators Caulk is not compatible with alkyd-paints.

This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. It is general in nature and does not constitute any liability. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application. In every case it is recommended to carry out preliminary experiments. The manufacturer reserves the right to modify products without prior notice.