

Technical datasheet



CONTRACTORS PVCu CLEANER

Product description

Contractors PVCu Cleaner is a highly effective, fast acting, non-smearing, liquid cleaning agent suitable for removing ingrained dirt and marks on white PVCu frames, trims and cladding.

Properties

- Fast acting
- Fast drying
- Ready to use
- Non-smearing
- Restores to a clear and shiny finish
- Perfumed
- Multi-purpose use
- Non-abrasive
- Highly flammable

Applications

- Cleaning of most types of white PVCu frames, sills, trims and cladding.
- For removing most ingrained dirt, grease, uncured sealant, pencil and pen mark.
- Cleaning of plastic garden furniture.

Technical data

Base	Solvent mixture	
Consistency	Fluid	
Density	0.791 g/cm³	
Application temperature	+5°C → +25°C	

Substrates

- Substrate condition Dirty
- Substrate preparation
 No pretreatment required.
- Suitable substrates
 White PVCu frames, sills, trims and cladding. Hard PVC.

Application method

Application method

For best results, apply and spread Contractors PVCu Cleaner onto surface with a clean, soft, colourfast cloth or paper tissue, working well into the surface. Leave to rest for a few minutes. Wipe away contamination and then polish the cleaned surface using a second dry cloth or paper tissue. Always work with a clean cloth to avoid contamination of the surface. Always wipe in one direction.







CONTRACTORS PVCu CLEANER

Health- and Safety Recommendations

Take the usual labour hygiene into account. Consult the packaging label and safety data sheet for more information.

Use only in well-ventilated areas.

Always wear gloves and goggles.

After contact with skin rinse immediately with soap and water.

Ingestion: rinse off the mouth with running water avoiding ingesting the liquid.

Get in touch with a doctor.

The user has to check if the product is suitable for the specific application.

Packaging/Logistics

Colour: Colourless Packaging: 1 L bottle

Shelf life: 24 months in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C.

Remarks

- It is recommended to do a compatibility test prior to application.
- Contractors PVCu Cleaner should not be diluted.

This technical data sheet replaces al previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. It is general in nature and does not constitute any liability. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application. In every case it is recommended to carry out preliminary experiments. The manufacturer reserves the right to modify products without prior notice.